


**AIR CONDITIONING**

# SRK17ZMP-S / DXK05Z5-S, 1.7KW



## KEY FEATURES

- Reverse Cycle model
- Rapid room cooling/heating with Hi Power mode
- Energy saving with Economy mode
- Dehumidification with Dry Operation mode
- Optional Wi-Fi control

Indoor			SRK17ZMP-S
Outdoor			SRC17ZMP-S
Power supply			1 Phase 220~240V 50Hz
Capacity	Cooling T1	kW	1.7 (0.9~2.7)
	Heating H1		2.0 (0.8~3.8)
Input	Cooling T1	kW	0.42 (0.25~0.94)
	Heating H1		0.465 (0.20~1.41)
Max running current		A	9
Energy label	Cooling T1	Stars	2.5
	Heating H1		4
EER	Cooling T1		4.05
COP	Heating H1		4.30
Sound power level (JIS C9612)	Cooling(Outdoor)	dB(A)	54
	Heating(Outdoor)		55
Sound pressure level (JIS C9612)	Cooling(Indoor)	dB(A)	45-34-23
	Heating(Indoor)		43-34-26
Airflow	Cooling(Indoor)	l/s	168-122-70
	Heating(Indoor)		158-122-87
External dimensions (HXWXD)	Indoor	mm	262x769x210
	Outdoor		540x645x275
Net weight	Indoor	kg	6.9
	Outdoor		25
Refrigerant piping	Liquid line	mm	Ø6.35
	Gas line		Ø9.52
	Connection method		Flare connection
Refrigerant R410A	Quantity	kg	0.655
	Pre charged to pipe length	m	10
Clean filter			Allergen Clear & Photocatalytic Washable Deodorizing Filter